# Safety Data Sheet Sodium Silicate Solution



**Section 1: Chemical Product and Company Identification** 

**Product Name:** Sodium Silicate Solution

CAS No.: 1344-09-8

**EC/EINECS:** 215-687-4

UN No: -

EC Annex1 Index No: -

Chemical Name: Sodium Silicate

Synonyms: Water glass, Silicic acid, Sodium salt

**Contact Information:** 

C.Thai Chemicals Co.,Ltd.

444 Moo 4 Petchakasem Rd.Omnoi, Krathumban, Samutsakorn, Thailand 74130 Phone number: 662-810-5090-9,662-420-5891-3

Fax number: 662-420-5894

Section 2: Hazards Identification

**GHS Classification:** Oral acute toxicity category 5

Skin irritation category 2 Eye irritation category 2A

**GHS Label:** 

**(!)** 

GHS Signal Word: Warning

GHS Precaution H303 May be harmful if swallowed

Phrases: H315 Causes skin irritation

H319 Causes serious eye irritation

**GHS Response** 

Phrases:

P312 Call a doctor if you feel unwell.

P302+P352 If on skin: Wash with plenty of soap and water.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362: Take off contaminated clothing and wash before reuse.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Emergency Overview: Clear, colorless, odorless, thick liquid. Causes eye, skin, and digestive tract irritation.

Spray mist causes irritation to respiratory tract. High pH is harmful to aquatic life. Noncombustible. Spills are slippery. Reacts with acids, ammonium salts, reactive

metals and some organics.

**Chronic hazards:** No known chronic hazards. Not listed by NTP, IARC or OSHA as a carcinogen.

Physical hazards: Dries to form glass film which can easily cut skin. Spilled material is very slippery.

Can etch glass if not promptly removed.

## Section 3: Composition and Information on Ingredients

Chemicals Characterization: molar ratio  $Na_2O: SiO_2 = 1: 2.00$  to 1: 3.20

Composition:

Name	CAS No.	EC No.	% by Weight
Sodium silicate	1344-09-8	215-687-4	29.50 – 53.85%
Water	7732-18-5	231-791-2	46.20 – 70.5%

Section	4.	Firet	Δid	Measures
Section	4.	гиэι	Alu	IVICabules

Eye Contact: Check for and remove any contact lenses. In case of contact, immediately flush eyes

with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

**Skin Contact:** Remove contaminated clothing and shoes. Wash with soap and water. Cover the

irritated skin with an emollient. Get medical attention if irritation develops.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

**Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give

anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie,

belt or waistband.

Serious Ingestion: Not available

## **Section 5: Fire and Explosion Data**

**Flammable limits:** This material is noncombustible.

**Extinguishing Media:** This material is compatible with all extinguishing media

Hazards to fire-fighters:

See Section 2 for information on hazards when this material is present in the area of a

fire.

Fire-fighting equipment:

The following protective equipment for fire fighters is recommended when this

material is present in the area of a fire: chemical goggles, body-covering protective

clothing, chemical resistant gloves, and rubber boots.

**Personal protection:** Wear chemical goggles, body-covering protective clothing, chemical resistant gloves,

and rubber boots. See section 8.

**Environmental** 

Hazards:

Sinks and mixes with water. High pH of this material is harmful to aquatic life.

#### **Section 6: Accidental Release Measures**

Small Spill: Mop up and neutralize liquid, then discharge to sewer in accordance with federal, state

and local regulations or permits.

Large Spill: Keep unnecessary people away; isolate hazard area and deny entry. Do not touch or

walk through spilled material. Stop leak if you can do so without risk. Prevent runoff from entering into storm sewers and ditches which lead to natural waterways. Isolate, dike and store discharged material, if possible. Use sand or earth to contain spilled material. If containment is impossible, neutralize contaminated area and flush with

large quantities of water.

Personal protection: Wear chemical goggles, body-covering protective clothing, chemical resistant gloves,

and rubber boots. See section 8.

**Environmental** Sinks and mixes with water. High pH of this material is harmful to aquatic life. See

**Hazards:** Section 12. Only water will evaporate from a spill of this material.

Section 7: Handling and Storage

**Handling:** Avoid contact with eyes, skin and clothing. Avoid breathing spray mist. Keep container

closed. Promptly clean residue from closures with cloth dampened with water.

Promptly clean up spills.

**Storage:** Keep containers closed. Store in clean steel or plastic containers. Separate from

acids.. Storage temperature 0-95° C. Loading temperature 20-95 °C. Do not store in

aluminum, fiberglass, copper, brass, zinc or galvanized containers.

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Use with adequate ventilation. Keep containers closed. Safety shower and

eyewash fountain should be within direct access.

**Personal Protection:** Wear chemical goggles, body-covering protective clothing and gloves.

**Section 9: Physical and Chemical Properties** 

Appearance: Liquid
Odor: Odorless.

Color: Clear to hazy white.

Specific Gravity at 20°C: 1.355 – 1.667
pH: 11.3 -12.3

Boiling Point: Not available.

Melting Point: Not available.

Flash Point: The product is not flammable

Critical Temperature: Not available.Oxidizing Properties: None oxidizer

**Photodegradation:** No photodegradation

Biodegradation: Not applicable (inorganic substances)

Solubility: Soluble in cold water, hot water.

Section 10: Stability and Reactivity Data

**Stability:** This material is stable under all conditions of use and storage.

Conditions of Instability: None.

Materials to avoid Gels and generates heat when mixed with acid.

Hazard decomposition product: -

**Section 11: Toxicological Information** 

Acute Data: When tested, sodium silicate 100% solids basis, it single dose acute oral LD50 in rats

ranged from 3,200 mg/kg to 8,650 mg/kg.

Skin Irritaion Data:

The irritation response is inversely correlated with the molar ratio of the silicates; a lower molar ratio SiO2: Na2O leads to a higher irritation score and vice versa. This correlation is superimposed by the concentration effect: lower concentrations will exhibit lower irritancy as compared to higher concentrations of the same molar ratio. Whereas ratios of 2.0 and 2.4

exhibited irritating properties, ratios of 2.8 and 3.3 were not irritating.

Eyes Irritation Data:

Varying molar ratios exhibited effects in enucleated rabbit eyes ranging from corrosive (MR 1.0) to severely irritating (MR 2.0, 2.4 and 2.6) to slightly irritating (MR 2.8, 3.0 and 3.3).

Subchronic Data:

Sodium Silicate study shows that no changes to rats' organ when feed for six month NOAEL

(180d) at 159 mg/kg bw/d

**Section 12: Ecological Information Ecotoxicity** 

**Ecotoxicity:** The following data is reported for chemically similar sodium silicates on a 100% solids

basis: LC50 (96 hour) for fish (Danio rerio) of 1108 ppm at MR 3.46; EC50 (48 hour) for invertebrates (Daphnia magna) of 1700 mg/l at MR 3.20; ErC50 and EbC50 (72 hour) for algae (Scenedesmus subspicatus) is 345 mg/l and 207 mg/l at MR 3.0; EC0 (18 hour) for

microorganisms (Pseudomonas putida) of 3480 mg/l at MR 3.46

Environmental Fate:

This material is not persistent in aquatic systems, but its high pH when undiluted or unneutralized is acutely harmful to aquatic life. Diluted material rapidly depolymerizes to yield dissolved silica in a form that is indistinguishable from natural dissolved silica. It does not contribute to BOD. This material does not bioaccumulate except in species that use silica as a structural material such as diatoms and siliceous sponges. Where abnormally low natural silica concentrations exist (less than 0.1 ppm), dissolved silica may be a limiting nutrient for diatoms and a few other aquatic algal species. However, the addition of excess dissolved silica over the limiting concentration will not stimulate the growth of diatom populations; their growth rate is independent of silica concentration once

the limiting concentration is exceeded.

**BOD5 and COD:** No COD or BOD impact on effluents.

**Section 13: Disposal Considerations** 

**Classification:** Disposed material is not a Hazardous waste.

**Disposal Method:** Dispose in accordance with federal, state and local regulations and permits.

**Section 14: Transport Information** 

**DOT UN Status:** This material is not regulated hazardous material for transportation.

Identification:Not applicable.Special Provisions for Transport:Not applicable.

**Section 15: Other Regulatory Information** 

**HMIS (U.S.A.):** Health Hazard: 1 Reactivity: 0

Fire Hazard: 0 Personal Protection:

National Fire ProtectionHealth: 1Reactivity: 0Association (U.S.A.):Flammability: 0Specific hazard:

**Protective Equipment:** Chemical goggles, Body-covering protective clothing and gloves.

#### **Section 16: Other Information References:**

Prepared by: Nichapa K. Rev.04 01 August 2017

**OECD SIDS: Soluble Silicate,** International Programme on Chemical Safety (IPCS): Chemical Safety Information from Intergovernmental Organization (INCHEM), France 20-23 April 2004

IUCLID Dataset Substance ID:1344-09-8, European Commission – European Chemicals Bureau, 18 Feb 2000

Soluble Silicate: Chemical, toxicological, ecological and legal aspects of production, transport, handling and application, European Chemical Industry Council, Belgium. Feb 2013

ESIS: European chemical Substances Information System, http://esis.jrc.ec.europa.eu/, 29 May 2014

International Chemical Safety Cards: Sodium Silicate (solution 25-50%), The National Institute for Occupational Safety and Health (NIOSH), http://www.cdc.gov/niosh/ipcsneng/neng1137.html, 20 June 2014

Alphabetical index of substances and articles, United Nations Recommendations on the Transport of Dangerous Goods (UNRTDG) http://www.unece.org/fileadmin/DAM/trans/danger/publi/unrec/rev14 /English/05E Index.pdf, 30 June 2014

THE INFORMATION ON THIS SAFETY DATA SHEET IS BELIEVED TO BE ACCURATE AND IT IS THE BEST INFORMATION AVAILABLE TO **C.THAI CHEMICALS CO.,LTD**. THIS DOCUMENT IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONS FOR HANDLING A CHEMICAL BY A PERSON TRAINED IN CHEMICAL HANDLING. **C. THAI CHEMICALS CO.,LTD** MAKES NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED WITH RESPECT TO SUCH INFORMATION OR THE PRODUCT TO WHICH IT RELATES, AND WE ASSUME NO LIABILITY RESULTING FROM THE USE OR HANDLING OF THE PRODUCT TO WHICH THIS SAFETY DATA SHEET RELATES. USERS AND HANDLERS OF THIS PRODUCT SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION PROVIDED HEREIN FOR THEIR OWN PURPOSES.